
MF-W1C0324F12RCVTF

Single phase AC regulator standard assembly

HIGHLIGHTS

- Axial fan
- Reliability
- Short delivery time
- Ultrafast fuse included
- Thermostat, snubber and varistor included
- Ready to use
- Working voltage up to 400 V_{RMS}
- Insulation 3000 V_{RMS}/1 min



Non-contractual image

GENERAL SPECIFICATIONS	
Nominal line to line input voltage (V_{RMS})	400 V_{AC} ±10%
Repetitive peak reverse voltage (V_{RRM})	1200 V_P
Maximum working current (I_{RMS}) (1)	324 A_{RMS} @ 35ºC TA
Maximum nominal working current (I_{RMS}) (2)	265 A_{RMS} @ 35ºC TA
Cooling	Forced air, fan 119x119 @ 230V_{RMS}

(1): The maximum non continuous w orking current

(2): The maximum continuous w orking current w ithout thermal protection activation

SEMICONDUCTOR SPECIFICATIONS	
Peak non-repetitive surge current (I_{TSM})	6000 A @ T_P=10ms, Tj=45ºC, (50Hz), sine
	5250 A @ T_P=10ms, Tj=125ºC, (50Hz), sine
I^2t capacity for fusing	180 kA^2s @ T_P=10ms, Tj=45ºC, (50Hz), sine
	137 kA^2s @ T_P=10ms, Tj=125ºC, (50Hz), sine
Maximum rate of rise of on-state current (repetitive) (di_T/dt)	150 A/µs
Maximum rate of rise of on-state current (non-repetitive) (di_T/dt)	500 A/µs
Maximum peak on-state voltage (V_{TM})	1,25 V @ I_{TM}=300A
Critical rate of rise of off-state voltage (dv/dt)	Min. 1000 V/µs @ Tj=125ºC, V_D=2/3 V_{RRM}
Gate trigger voltage (V_{GT})	max. 2,5 V @ Tj=25ºC, V_D=6V
	max. 2,6 V @ Tj=-40ºC, V_D=6V
Gate trigger current (I_{GT})	max. 150 mA @ Tj=25ºC, V_D=6V
	max. 200 mA @ Tj=-40ºC, V_D=6V
Latching current (I_L)	300 mA @ Tj=25ºC, t_P=30µs; V_D=6V
Holding current (I_H)	200 mA @ Tj=25ºC; V_D=6V

PROTECTION	
dv/dt protection (RC)	RC network 0,068µF/150 Ohms
Peak voltage protection (VDR)	460 V_{RMS} varistor
Current protection (Semiconductor fuses) (1)	070GUDA0350F
Microswitch (fuse indicators)	MS4L 2-5 B6
Thermal protection (Thermostats)	70ºC NC

(1): Fuses only for shortcircuit protection. User provide external protection for continuous overloads and cable size.

200616 Rev.:1

RECTIFICADORES GUASCH, S.A.U.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

TERMINAL SPECIFICATIONS	
Input power terminals (AC terminals)	(M8) 8 to 12 Nm
Module power terminals	(M6) 4,5 to 5,5 Nm
Output power terminals	2xØ8,5 (M8) 11 to 13 Nm (1)
Control & auxiliary terminals	WAGO series 260 terminal blocks 1,5 mm^2 / AWG 16


(1):The press should be performed w ith tw o keys, avoiding to transmit lateral efforts al terminal of connection, w hat w ould be able to produce the deterioration of the element semiconductor.

ENVIRONMENT SPECIFICATIONS	
Protection grade (EN-60529 / CEI529 / UNE-20324)	IP-00
Humidity max.	50% RH @ 35ºC / 90% RH @ 20ºC
Pollution degree	III
Isolation	3000 V_{RMS} / 1 min

LOSSES	
Power dissipation of semiconductors at full charge	Aprox. 292 W
Maximum power dissipation of fuse at full charge	Aprox. 28 W
Maximum total power dissipation at full charge	Aprox. 320 W

MECHANICAL SPECIFICATIONS	
Mounting position	Any
Storage temperature	-25 to 80ºC
Width	250 mm
Depth	267 mm
Height	228 mm
Aprox. Weight	4,4 Kg.

SCHEMATIC CIRCUIT




200616 Rev.:1

RECTIFICADORES GUASCH, S.A.U.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN


Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.


Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

MECHANICAL DIMENSIONS



(All units in mm)





200616 Rev.:1

RECTIFICADORES GUASCH, S.A.U.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

MOUNTING CONSIDERATIONS

It's necessary a minimum distance of 100 mm with regard to the envelope. The free air circulation should be guaranteed. Avoiding the heat sources of nearby to assembly.

In the real applications it is important to consider a safety margin with regarding the working current, we recommend a margin of the 20%.

For critical cases (24 hours work, repetitive overloads...), margins of the 30% to 50% are used.

ORDER CODES & OPTIONS

MF- W1C 0324 F 12 RCVTF
(1) (2) (3) (4) (5) (6)

1- MF, Series identifier
2- W1C, Circuit identifier
3- 0324; Maximum current identifier
4-F, Refrigeration identifier (N:Natural; F: Forced)
5-12; V_{RRM}/10 identifier
6-Accesories:
RC: Resistance-capacitor (snubber) included
V: Varistor included
T. Thermal switch included
F: Semiconductor fuse protection included. (fuse also includes microswitch)


200616 Rev.:1


RECTIFICADORES GUASCH, S.A.U.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN


Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.


Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

GRAPHICAL INFORMATION









200616 Rev.:1

RECTIFICADORES GUASCH, S.A.U.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

ANOTACIONES EN LA HOJA DE ESPECIFICACIONES:

RECTIFICADORES GUASCH, S.A.U. utiliza la siguiente anotación para identificar el estado del producto, en el lado izquierdo de la primera página:

PRELIMINARY TECHNICAL INFORMATION: El producto se encuentra en proceso de diseño y desarrollo. La información presenta los datos del producto pero algunas características pueden cambiar.

ADVANCED TECHNICAL INFORMATION: El producto se encuentra totalmente diseñado y las características se refieren a la fabricación en serie.

Sin anotación: Los parámetros del producto están fijados y se suministra de acuerdo con las especificaciones publicadas.

Los datos indicados en esta publicación corresponden a especificaciones de producto, queda excluida cualquier garantía expresa o implícita sobre sus propiedades o su aplicación, así como cualquier responsabilidad sobre daños directos o indirectos producidos por los materiales o resultantes de su aplicación. La empresa se reserva el derecho de realizar cambios en las especificaciones de los productos sin previo aviso. La información respecto a métodos de uso y aplicaciones se indica sólo como guía y no constituye garantía alguna de funcionamiento satisfactorio en un determinado equipo o aplicación. Es responsabilidad del usuario determinar la idoneidad del producto para su aplicación utilizando la información disponible y asegurarse de que la misma esta actualizada.
Cualquier nombre de producto o marca usada en esta publicación corresponde a marcas depositadas, marcas registradas o nombres protegidos por sus respectivos propietarios.

DATASHEET ANNOTATIONS:

RECTIFICADORES GUASCH, S.A.U. annotate datasheets in the left corner of the front page, to indicate product status:

PRELIMINARY TECHNICAL INFORMATION: The product is in design and development. The datasheet represents the product as it is understood but details may change.

ADVANCED TECHNICAL INFORMATION: The product design is complete and final characterisation for volume production is well in hand.

No Annotation: The product parameters are fixed and the product is available to datasheet specification.

The technical data are to specify components, not to guarantee their properties. No warranty or guarantee expressed or implied is made regarding delivery or performance. The Company reserves the right to alter without prior notice the specification of any product. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date.
All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.

© RECTIFICADORES GUASCH, S.A.U.
DOCUMENTACION TECNICA, TECHNICAL DOCUMENTATION
PRODUCIDO EN ESPAÑA, PRODUCED IN SPAIN
PROHIBIDA SU VENTA, NOT FOR SALE

Your Needs, Our Solutions

200616 Rev.:1

RECTIFICADORES GUASCH, S.A.U.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com