PRELIMINARY TECHNICAL INFORMATION




Foto no contractual / Photo non-contractual

HIGHLIGHTS

-Wide range.
-Reliability.
-Short delivery time
-Modular system.
-Cooling system included.
-Current, voltage and temperature sensors.
-IGBT drivers included.
-Ready to use.


ABOUT MT SERIES

RECTIFICADORES GUASCH S.A. offers the most modulable way for designing power stages AC-AC or DC-AC by connecting rectifier block, DC-link block and IGBT power stack. This way, the customer (and not the builder) decides which the block that limits the power of the entire system. The customer can obtain in a short delivery time a wide range of power assemblies in a compact size.

Each block is designed for obtaining the maximum efficiency by itself in the minimum dimensions. MT series is suitable to realize converters, choppers, half, full or three phases bridge inverters for motor control, welding, renewable energies, UPS...

BRIEFING

Topology	B2I	
Market	industrial	
Cooling system	centrifugal fan	
Driver system	SCiCoreLink67	
Parameters monitorized	DC voltage, Output current (each phase) temperature on heatsink	
Max Voltage applied to DClink		1100 V
Output current per phase	fsw=5kHz, TJ<125ºC Tamb=40ºC *fo=50Hz P.F.=0.85 m=1 VDClink=900V*	175 A



091019Rev.:0

RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

POWER STACK GENERAL CHARACTERISTICS

Description	*symbol*	*notes/test conditions*	*Min*	*Typ*	*Max*	*Units*
Voltage applied to DClink	V_{DClink}	**note 1**		900	1200	V_{DC}
Output current per phase	$I_{U,V,W}$	fsw=5kHz, TJ<125ºC Tamb=40ºC fo=50Hz P.F.=0.85 m=1 VDClink=900V			175	A_{RMS}
IGBT maximum junction temperature	T_{Jmax}				150	ºC
IGBT temp. under switching conditions	$T_{J\ (sw)}$		-40		125	ºC
Storage temperature	T_{stg}		-40		85	ºC
Operating temperature	T_{op}		-25		85	ºC
Power-to-control isolation voltage	V_{ISOp-c}	50 Hz @1min/ **note 2**	3			kV_{AC}
Module isolation voltage	V_{ISOmod}	50 HZ @1min/ **note 3**	3,4			kV
Mounting Torque AC terminals		M6	4.5		5.5	N·m
Mounting Torque DC terminals		M6	4.5		5.5	N·m
Mounting Torque Capacitor Bank		M6	4.5		5.5	N·m
Weight (aprox)				13.7		kg

COOLING SYSTEM CHARACTERISTICS

Description	*symbol*	*notes/test conditions*	*Typical*	*Units*
Type		centrifugal fan		
Fan system supply voltage	V_{FAN}		230	V_{RMS}
Fan system consumption	I_{FAN}	50Hz/60Hz	0,92/0,89	A

IGBT MODULE ELECTRICAL CHARACTERISTICS

Description	*symbol*	*notes/test conditions*	*Min*	*Typ*	*Max*	*Units*
Collector-Emitter Voltage	V_{CES}	T_J=25ºC			1700	V
DC Collector current	I_{Cnom}	T_C=80ºC, T_J=150ºC			300	A
Repetitive peak collector current	I_{CRM}	t_p=1ms			600	A
Power dissipation (per module)	P_{DISS}	T_C=25ºC, T_J=150ºC			1450	W
Collector-emitter saturation voltage	V_{CEsat}	Ic=300 A, TJ=125ºC		2,4		V

***note 1**: This voltage is limited by IGBT module restricted by DC Link capacitors voltage.*
***note 2**: This isolation voltage is referred to the minimum isolation voltage between any control/feedback signal (PWM, reset fault, feedback sensor signals and supply of boards) and any power voltage (DC input, AC output).*
***note 3**: This is an inner property of the IGBT module. It refers to the isolation between the internal chip and the external case.*

091019 Rev.:0

RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

ENVIRONMENTAL SPECIFICATIONS

Description	
Protection grade (EN-60529 / CEI529 / UNE-20324)	IP-00
Humidity max.	50% RH @ 35ºC / 90% RH @ 20ºC
Pollution degree	III

MOUNTING CONSIDERATIONS

It's necessary a minimum distance of 100 mm with regard to the envelope. The free air circulation should be guaranteed. Avoiding the heat sources of nearby to assembly.

In the real applications it is important to consider a safety margin with regarding the working current, we recommend a margin of the 20%.

For critical cases (24 hours work, repetitive overloads...), margins of the 30% to 50% are used.


RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN


Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com


Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

MECHANICAL DIMENSIONS


All dimensions in mm.








All holes M6 threaded






091019 Rev.:0

RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.


Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

POWER CONNECTION



CAPACITOR BANK ADAPTATION

CONTROL CONNECTION



091019Rev.:0

RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com


GATE DRIVER BOARD ELECTRICAL CHARACTERISTICS

Description	*symbol*	*notes/test conditions*	*Min*	*Typ*	*Max*	*Units*
Supply voltage	V_{CC}			15		V
Current consumption	Icc	f_{sw}=10kHz; $Q_{G/pulse}$=6μC		370		mA
PWM & reset High state Input voltage	V_{IN_H}	JP1 to 5V connected	3,5		5	V
PWM & reset Low state Input voltage	V_{IN_L}	JP1 to 5V connected	0		1,5	V
PWM & reset High state Input voltage	V_{IN_H}	JP1 to 15V connected	11		15	V
PWM & reset Low state Input voltage	V_{IN_L}	JP1 to 15V connected	0		4	V
Fault High state Output Voltage	V_{FAULT_H}	working in logic lev; JP1 to 15V			15	V
Fault High state Output Voltage	V_{FAULT_H}	working in logic lev; JP1 to 5V			5	V
Fault (working as open collector) current	I_{FAULT}	working as open collector			20	mA

GATE DRIVER BOARD PINOUT

CON 1	*designation*	*function*
1	PWM_{TOP}	Input logic signal for switching TOP IGBT
2	GND	Ground terminal for supply and logic signals
3	GND	Ground terminal for supply and logic signals
4	RESET	reset input signal (low state
5	GND	Ground terminal for supply and logic signals
6	VCC	+15VDC for supply voltage
7	FAULT	fault output signal
8	VCC	+15VDC for supply voltage
9	VCC	+15VDC for supply voltage
10	PWM_{BOT}	Input logic signal for switching BOT IGBT

JUMPERS	
JP1	right connected: 15V logic level left connected: 5V logicc level
JP2	right connected: half bridge mode left connected: direct mode



All dimensions in mm.

DEFAULT VALUES

· half bridge mode (direct mode optional)
· 4μs dead time between channels generated
· Gate resistor depending of the IGBT module used
· 0-5V input PWM and reset logic levels (0-15V optional)
· 0-5V logic fault output (0-15V or low level-open collector fault output optional)

091019 Rev.:0


RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN


Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com


Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

SENSOR BOARD ELECTRICAL CHARACTERISTICS

Description	*symbol*	*notes/test conditions*	*Min*	*Typ*	*Max*	*Units*
Supply voltage	V_{CC}			±15		V
Feedback signal of heatsink temp.	V_T	relative error <2,5%	0		12	V
Heatsink temp. measurable range			0		120	ºC
Feedback signal of output current	V_{CX}	relative error <3%	0		10	V
Current measurable range			-600		600	A
Feedback signal of VDC-link voltage	V_U	relative error <2,8%	0		15	V
DC-link measurable voltage range			0		1500	V_{DC}
Thermostat		Normally connected		90		
NTC rated resistance	$R_{NTC\ 25}$					kΩ
NTC B value	$B_{25/50}$					K








SENSOR BOARD PINOUT

CON 2	*designation*	*function*
1	+15Vcc	+15VDC for supply voltage
2	N.C.	
3	N.C.	
4	N.C.	
5	N.C.	
6	N.C.	
7	N.C.	
8	TH_2	Thermostat terminal 2
9	V_T	Output voltage representation of heatsink temperature
10	TH_1	Thermostat terminal 1
11	$V_{C\ B}$	Output voltage representation of heatsink temperature
12	V_U	Output voltage representation of VDC-link voltage
13	$V_{C\ C}$	Output voltage representation of phase C output current
14	$V_{C\ A}$	Output voltage representation of phase A output current
15	-15Vcc	-15VDC for supply voltage



091019Rev.:0

RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN


Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

PERFORMANCE CURVES

Stack working as an inverter

T_{J_IGBT} **vs** I_{OUT} (per phase, AC output)



Condition	*Symbol*	*Value*	*Units*
Ambient temperature	T_A	40	ºC
DClink Voltage	V_{DClink}	900	V
Load Power Factor	PF	0,85	
Modulation index	m	1	
Output frequency	f_{OUT}	50	Hz

091019 Rev.:0

RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

ANOTACIONES EN LA HOJA DE ESPECIFICACIONES:

RECTIFICADORES GUASCH, S.A. utiliza la siguiente anotacion para identificar el estado del producto, en el lado izquierdo de la primera página:

PRELIMINARY TECHNICAL INFORMATION: El producto se encuentra en proceso de diseño y desarrollo. La información presenta los datos del producto pero algunas características pueden cambiar.
ADVANCED TECHNICAL INFORMATION: El producto se encuentra totalmente diseñado y las características se refieren a la fabricación en serie.

Sin anotación: Los parámetros del producto están fijados y se suministra de acuerdo con las especificaciones publicadas.

Los datos indicados en esta publicación corresponden a especificaciones de producto, queda exlcuida cualquier garantía expresa o implícita sobre sus propiedades o su aplicación, así como cualquier responsabilidad sobre daños directos o indirectos producidos por los materiales o resultantes de su aplicación. La empresa se reserva el derecho de realizar cambios en las especificaciones de los productos sin previo aviso. La información respecto a métodos de uso y aplicaciones se indica sólo como guía y no constituye garantia alguna de funcionamiento satisfactorio en un determinado equipo o aplicación. Es responsabilidad del usuario determinar la idoneidad del producto para su aplicación utilizando la información disponible y asegurarse de que la misma esta actualizada.

Cualquier nombre de producto o marca usada en esta publicación corresponde a marcas depositadas, marcas registradas o nombres protegidos por sus respectivos propietarios.

DATASHEET ANNOTATIONS:

RECTIFICADORES GUASCH, S.A. annotate datasheets in the left corner of the front page, to indicate product status:

PRELIMINARY TECHNICAL INFORMATION: The product is in design and development. The datasheet represents the product as it is understood but details may change.
ADVANCED TECHNICAL INFORMATION: The product design is complete and final characterisation for volume production is well in hand.

No Annotation: The product parameters are fixed and the product is available to datasheet specification.

The technical data are to specify components, not to guarantee their properties.No warranty or guarantee expressed or implied is made regarding delivery or performance. The Company reserves the right to alter without prior notice the specification of any product. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date.

All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.

DATASHEET ANNOTATIONS:

RECTIFICADORES GUASCH, S.A. Indiqué dans la notice technique a la part inferieur à gouche le suivant pour vous informer de la situation du produits

PRELIMINARY TECHNICAL INFORMATION: Le produit est dans la conception et le développement. La notice technique représente le produit comme il a été conçu mais les détails peuvent changer.
ADVANCED TECHNICAL INFORMATION: La conception de produit est fini et la notice technique est comme il a été conçu pour la fabrication.

Sans annotation: La notice technique indique que le produit est selon la même

Les donnes indiques dans la notice technique sont conformément aux spécifications des composants, sont exclues toutes autres conditions ou garanties exprimées ou implicites concernant la qualité et le bon fonctionnement des matériels, ainsi que toute responsabilité pour les dommages causés directement ou indirectement par les matériels ou résultant de leur utilisation. Nous nous reservons la possibilite de changement sans notification. L'information à propos des méthodes possibles d'usage est fournie comme un guide conformemente aux spécifications et instructions et ne constitue pas garantie que telles méthodes d'usage sera satisfaisant dans un morceau spécifique d'équipement. C'est la responsabilité de l'Acheteur déterminer l'exécution et l'aptitude du produit et s'assure qu'il a la darriere actualisation de la notice technique.

Des noms de marque et produit utilisés dans cette publication sont enregistrées et propriété de leurs propriétaires respectifs.

© RECTIFICADORES GUASCH, S.A.

DOCUMENTACION TECNICA, TECHNICAL DOCUMENTATION, DOCUMENTATION TECHNIQUE
PRODUCIDO EN ESPAÑA, PRODUCED IN SPAIN, PRODUIT EN ESPAGNA
PROHIBIDA SU VENTA, NOT FOR SALE, PAS A VENDRE

Your Needs, Our Solutions

091019Rev.:0

RECTIFICADORES GUASCH, S.A.
Ciutat de Granada, 80
08005 BARCELONA
SPAIN

Tel.: +34 93 309 88 91
Fax.: +34 93 300 18 41
e-mail: info@e-guasch.com
www.e-guasch.com

Se reserva el derecho de cambiar los límites, las condiciones de prueba y dimensiones indicadas en esta hoja sin previo aviso.
Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.