
MTM-B6I0200F12LSBA

IGBT power stack

PRELIMINARY TECHNICAL INFORMATION

HIGHLIGHTS

- Wide range.
- Reliability.
- Short delivery time
- Modular system.
- Cooling system included.
- Current, voltage and temperature sensors.
- IGBT drivers included.
- Ready to use.



non-contractual photo

Please read before the document "MTM series complete datasheet" for further information about dimensions, connections, drivers, sensor system and more.


BRIEFING

Topology	B6I
Market	industrial
Sensor system	SCiSensor153
Driver system	SCiCoreLink62
Parameters monitorized	DC voltage, output current (each phase) temperature on heatsink
Voltage class	1200 V
Output current per phase (1)	190 A

(1): stack working as a sinusoidal inverter with f_{sw}=5 kHz, T_J<125ºC T_{AMB}=40ºC, f_{OUT}=50Hz P.F.=0.85 m=1 VDClink=600 V.

About MTM series

IGBT inverter stacks from 40 kW to 250 kW in B2I and B6I topologies with medium-range power IGBT modules. Gate drivers, current, voltage and temperature sensors included along sensor concentrator-adaptator board. Control signals fan-out are isolated from power to user interface. Optical interface also available.



130205 Rev.:0

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

MODULE ELECTRICAL CHARACTERISTICS

description	symbol	conditions & notes	min	typ	max	units
IGBT						
Collector-Emitter voltage	V_{CES}	T_J=25ºC			1200	V
DC collector current	I_{Cnom}	T_C=80ºC, T_J=150ºC			200	A
Collector-emitter saturation voltage	V_{CEsat}	Ic=200 A, T_J=125ºC		2.4		V
FREE-WHEELING DIODE						
Emitter-collector voltage	V_{EC}	T_J=25ºC			1200	V
DC forward current	I_F	T_C=80ºC, T_J=150ºC			200	A
Forward voltage	V_F	Ic=200 A, T_J=125ºC		1.90		V
MODULE						
maximum junction temperature	T_{Jmax}				150	ºC
Module isolation voltage	V_{ISO}	50 Hz @ 1min (2)	2500			V

ANALOG SIGNALS OUTPUT


description	symbol	conditions & notes	min	typ	max	units
DC Voltage analog signal	V_{UDC}	*1V/100V_{DClink}*	0		15	V
Output current analog signal	V_{IOUT}	*5V+(1V/133A)*	0		10	V
Heatsink temperature analog signal	V_{THK}	*1V/10ºC*	0		12	V

Please refer to "MTM series complete datasheet" for further information.

PERFORMANCE CURVES

stack working as a sinusoidal inverter.

T_{J_IGBT} vs I_{OUT} (per phase, AC output)



V_{DC}	V_{OUT}	cos fi	f_{SW}	f_{OUT}	T_J	T_{AMB}
V_{DC} typ	400 V_{RMS} (1200V class)	0.85	parameter	50Hz	125ºC	40ºC

(2): This is an inner property of the IGBT module. It refers to the isolation between the internal chip and the external case.

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

ANOTACIONES EN LA HOJA DE ESPECIFICACIONES:

RECTIFICADORES GUASCH, S.A. utiliza la siguiente anotación para identificar el estado del producto, en el lado izquierdo de la primera página:

PRELIMINARY TECHNICAL INFORMATION: El producto se encuentra en proceso de diseño y desarrollo. La información presenta los datos del producto pero algunas características pueden cambiar.
ADVANCED TECHNICAL INFORMATION: El producto se encuentra totalmente diseñado y las características se refieren a la fabricación en serie.
Sin anotación: Los parámetros del producto están fijados y se suministra de acuerdo con las especificaciones publicadas.

Los datos indicados en esta publicación corresponden a especificaciones de producto, queda exlcuida cualquier garantía expresa o implícita sobre sus propiedades o su aplicación, así como cualquier responsabilidad sobre daños directos o indirectos producidos por los materiales o resultantes de su aplicación. La empresa se reserva el derecho de realizar cambios en las especificaciones de los productos sin previo aviso. La información respecto a métodos de uso y aplicaciones se indica sólo como guía y no constituye garantía alguna de funcionamiento satisfactorio en un determinado equipo o aplicación. Es responsabilidad del usuario determinar la idoneidad del producto para su aplicación utilizando la información disponible y asegurarse de que la misma esta actualizada.
Cualquier nombre de producto o marca usada en esta publicación corresponde a marcas depositadas, marcas registradas o nombres protegidos por sus respectivos propietarios.

DATASHEET ANNOTATIONS:

RECTIFICADORES GUASCH, S.A. annotate datasheets in the left corner of the front page, to indicate product status:

PRELIMINARY TECHNICAL INFORMATION: The product is in design and development. The datasheet represents the product as it is understood but details may change.
ADVANCED TECHNICAL INFORMATION: The product design is complete and final characterization for volume production is well in hand.
No Annotation: The product parameters are fixed and the product is available to datasheet specification.

The technical data are to specify components, not to guarantee their properties. No warranty or guarantee expressed or implied is made regarding delivery or performance. The Company reserves the right to alter without prior notice the specification of any product. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date.
All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.

© RECTIFICADORES GUASCH, S.A.
DOCUMENTACION TECNICA, TECHNICAL DOCUMENTATION
PRODUCIDO EN ESPAÑA, PRODUCED IN SPAIN
PROHIBIDA SU VENTA, NOT FOR SALE

Your Needs, Our Solutions