
RGHVVCS220...

High voltage valve clamp system

OVERVIEW

-High reliability
-Even pressure distribution.
-Easy mounting.
-Isolation with high strength composite rods.
-Clamping range available from 4500 Kgf to 14000 Kgf.
-Clamping force tolerances: -5% +10%
-Maximum semiconductor external diameter: Ø195 mm.
-Free space between rods: 165 mm.
-Maximum set of series semiconductor thickness: 1500 mm.



non-contractual image


GENERAL DESCRIPTION

The system is composed of 2 clamp heads and a set of high strength composite threaded rods, the length of these rods defines the thickness "M" of the set of series semiconductors (see dimensions and ordering information).

Force are pre-calibrated and following the mounting recommendations it is not necessary to use special tools for tightening.

if an independent isolation of the heads is necessary, the interposition of an isolation system (not supplied because it depends on the design of the application) must be taken into account.


DIMENSIONS AND ORDERING INFORMATION



Clamp head detail

120123 Rev.:0

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.



01- Pressure indicator
It indicates the moment in which the adequate pressure is being performed during the assembly (this pressure is the correct one when you can move the indicator slightly).

02- Clamp head
It supports the series semiconductor and pressure set, it is manufactured in aluminium with rounded edges.

03-Mounting rod
Made by high strength composite M24 threaded rods and nuts, it ensures the necessary insulation between the 2 clamp heads for high voltage applications.

04-Tightening nuts
Clamp tightening nuts (M12) for apply the compression force.

Ordering information (example):

RGHVVCS220/9600/320

"**RGHVVCS220**": Type identification

"**9600**": Pre-calibrated force in Kgf (available from 4500 to 14500 Kgf)

"**320**": "M" dimension.

120123 Rev.:0

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

MOUNTING INSTRUCTIONS

For mounting the clamps RGHVVCS220 are used three threaded rods for the pressuring of (M12). It works by means of an elastic system that pressures the centre of the device and doesn't require any special tool for correct mounting, This is because a precalibrated force indicator is included for safe and easy mounting in your power stack.

Please follow the next steps in order to avoid any problem while mounting it.

1-Clean carefully the contact surfaces of the heat sinks or bus-bars.

2-Arrange small amount of thermal conductive paste on a flat surface (glass or similar), TCZn-60 is recommended and available in our online power store, spread with the help of a foam roller.

3-With roller impregnated paste "paint" the contact surfaces of the semiconductor, must a thin layer (ideally 50µ to 100µ).

4-Place the devices onto the heat sinks.

5-Assemble the clamp connecting the series heat sinks and devices.

6-Tighten the composite bolts alternatively until the central spreader contact part is perfectly aligned with the assembly, apply only the force for maintain the assembly stable.

7-Tighten pressure nuts alternately by 1/8 turn, checking the pressure indicator tab each time until just turns free.

8-Check again the pressure indicator after 120 minutes. If necessary, tighten slightly.

WARNING

Do not over-tighten. If it occurs, completely loosen the clamp, allow the clamp spring washers to relax for 1/2 hour and proceed to re-tighten it. Make sure that the device is not damaged.

Do not move the centre nut of the head clamp, pre-calibrated be lost.

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

ANOTACIONES EN LA HOJA DE ESPECIFICACIONES:

RECTIFICADORES GUASCH, S.A. utiliza la siguiente anotación para identificar el estado del producto, en el lado izquierdo de la primera página:

PRELIMINARY TECHNICAL INFORMATION: El producto se encuentra en proceso de diseño y desarrollo. La información presenta los datos del producto pero algunas características pueden cambiar.
ADVANCED TECHNICAL INFORMATION: El producto se encuentra totalmente diseñado y las características se refieren a la fabricación en serie.
Sin anotación: Los parámetros del producto están fijados y se suministra de acuerdo con las especificaciones publicadas.

Los datos indicados en esta publicación corresponden a especificaciones de producto, queda exlcuida cualquier garantía expresa o implícita sobre sus propiedades o su aplicación, así como cualquier responsabilidad sobre daños directos o indirectos producidos por los materiales o resultantes de su aplicación. La empresa se reserva el derecho de realizar cambios en las especificaciones de los productos sin previo aviso. La información respecto a métodos de uso y aplicaciones se indica sólo como guía y no constituye garantía alguna de funcionamiento satisfactorio en un determinado equipo o aplicación. Es responsabilidad del usuario determinar la idoneidad del producto para su aplicación utilizando la información disponible y asegurarse de que la misma esta actualizada.
Cualquier nombre de producto o marca usada en esta publicación corresponde a marcas depositadas, marcas registradas o nombres protegidos por sus respectivos propietarios.

DATASHEET ANNOTATIONS:

RECTIFICADORES GUASCH, S.A. annotate datasheets in the left corner of the front page, to indicate product status:

PRELIMINARY TECHNICAL INFORMATION: The product is in design and development. The datasheet represents the product as it is understood but details may change.
ADVANCED TECHNICAL INFORMATION: The product design is complete and final characterisation for volume production is well in hand.
No Annotation: The product parameters are fixed and the product is available to datasheet specification.

The technical data are to specify components, not to guarantee their properties.No warranty or guarantee expressed or implied is made regarding delivery or performance. The Company reserves the right to alter without prior notice the specification of any product. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date.
All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.

© RECTIFICADORES GUASCH, S.A.
DOCUMENTACION TECNICA, TECHNICAL DOCUMENTATION, DOCUMENTATION TECHNIQUE
PRODUCIDO EN ESPAÑA, PRODUCED IN SPAIN, PRODUIT EN ESPAGNA
PROHIBIDA SU VENTA, NOT FOR SALE, PAS A VENDRE

Your Needs, Our Solutions

120123 Rev.:0