
PRELIMINARY TECHNICAL INFORMATION

Signal conditioner for MTH-series sensors + voltage transducer



non-contractual photo


HIGHLIGHTS


-Heatsink temperature signal conditioning
-Up to 3 output phase current signal conditioning
-DC-link voltage measuring (up to1500V_{DC})
-Mechanical adaption for connect up to 3 internal modules NTC's and a thermostat


SCi*sensor*153A is signal conditioner board designed for conditioning the electrical output signals of the sensors included in the MTH-series**.** It also includes the voltage transducer. **SCi*sensor*153A** concentrates all the necessary feedback signals (for monitoring and control) in a single connector.

ELECTRICAL CHARACTERISTICS

Description	*symbol*	*notes/test conditions*	*Min*	*Typ*	*Max*	*Units*
Supply voltage	V_{CC}			±15		V
Feedback signal of heatsink temp.	V_T	relative error <2,5%	0		12	V
Heatsink temp. measurable range			0		120	ºC
Feedback signal of output current	V_{CX}	relative error <3%	0		10	V
Current measurable range			-2400		2400	A
Feedback signal of VDC-link voltage	V_U	relative error <2,8%	0		15	V
DC-link measurable voltage range			0		1500	V_{DC}








091106Rev.:0

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

CON1	designation	function
1	+15Vcc	+15V_{DC} for supply voltage
2	NTCU1	NTC terminal 1 of IGBT module U
3	NTCV2	NTC terminal 2 of IGBT module V
4	NTCV1	NTC terminal 1 of IGBT module V
5	NTCW1	NTC terminal 1 of IGBT module W
6	NTCU2	NTC terminal 2 of IGBT module U
7	NTCW2	NTC terminal 2 of IGBT module W
8	TH_2	Thermostat terminal 2
9	V_T	Output signal of heatsink temp.
10	TH_1	Thermostat terminal 1
11	V_{C_V}	Output signal of phase V output current
12	V_U	Output signal of VDC-link voltage
13	V_{C_W}	Output signal of phase W output current
14	V_{C_U}	Output signal of phase U output current
15	-15Vcc	-15V_{DC} for supply voltage
16	GND	Ground terminal for supply and signal

connector CON1: type TYCO 1-1634688-6
connector JTH, JN1, JN2, JN3: type MOLEX 22-27-2021
connector JT: type MOLEX 22-27-2031
connector JVDC,JC1, JC2, JC3: type MOLEX 22-27-2041

JVDC:1	to R+ V_{DC}link voltage sensing
JVDC:2	N.C.
JVDC:3	N.C.
JVDC:4	to R- V_{DC}link voltage sensing
JT:1	to V- HTS system
JT:2	to ADJ HTS system
JT:3	to V+ HTS system
JC1:1	GND for HAT 800-S (1)
JC1:2	output signal from HAT 800-S (1)
JC1:3	-15V_{DC} to supply HAT 800-S (1)
JC1:4	+15V_{DC} to supply HAT 800-S (1)
JC2:1	GND for HAT 800-S (2)
JC2:2	output signal from HAT 800-S (2)
JC2:3	-15V_{DC} to supply HAT 800-S (2)
JC2:4	+15V_{DC} to supply HAT 800-S (2)
JC3:1	GND for HAT 800-S (3)
JC3:2	output signal from HAT 800-S (3)
JC3:3	-15V_{DC} to supply HAT 800-S (3)
JC3:4	+15V_{DC} to supply HAT 800-S (3)
JN1:1	to internal module NTC 1 (A)
JN1:2	to internal module NTC 1 (B)
JN2:1	to internal module NTC 2 (A)
JN2:2	to internal module NTC 2 (B)
JN3:1	to internal module NTC 3 (A)
JN3:2	to internal module NTC 3 (B)
JTH:1	to thermostat (A)
JTH:2	to thermostat (B)




All dimensions are in mm

091106Rev.:0

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.

APPLICATION EXAMPLE



091106Rev.:0

Reserves the right to change limits, test conditions and dimensions given in
this data sheet at any time without previous notice.

Cost Effective Products

SEMICODE ELECTRONICA

offers to the market a comprehensive range of products from recognized manufacturers at the best price/ quality relationship, this products are provided with a basic reference code that allows maintaining the same product reference even if the original device manufacturer is replaced. SEMICODE product reference has to be considered as a generic brand.

Seeking the market needs and trends, we are constantly increasing the product portfolio with new products and suppliers, please ask for the updated information available to our local contacts.

SEMICODE products include semiconductors, passive components and accessories focused in power electronics market.

Datasheet Annotations:

SEMICODE ELECTRONICA annotate datasheets in the top left hard corner of the front page, to indicate product status. The annotations are as follows:
Tentative information: This is the most tentative form of information and represents a very preliminary specification. No actual design work on the product has been started.
Preliminary Information: The product is in design and development. The datasheet represents the product as it is understood but details may change.
Advance Information: The product design is complete and final characterisation for volume production is well in hand.
No Annotation: The product parameters are fixed and the product is available to datasheet specification.

NOTICE: The technical data are to specify components, not to guarantee their properties.No warranty or guarantee expressed or implied is made regarding delivery or performance. The Company reserves the right to alter without prior notice the specification of any product. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date.

All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.

© SEMICODE ELECTRONICA 2008. TECHNICAL DOCUMENTATION – NOT FOR RESALE

091106Rev.:0

Reserves the right to change limits, test conditions and dimensions given in this data sheet at any time without previous notice.